

Leica MDS05/20/30

Docking station for MCP80

Data sheet



Data storage

The in-cabin mounted Leica MDS docking stations store machine specific data such as calibration values and hydraulic parameters. This enables the operator to use the panel on any other machine without the risk of losing machine data. Furthermore, the docking station handles all cable connections, making the Leica MCP80 panel completely cable-free. Charging of the panel as well as all data transfer happens via infrared link.



Robust Design

Its robust design and structure makes the MDS05/20/30 docking station prepared for even the harshest environment. The cast aluminium housing absorbs vibration, thus reducing wear and tear. Rated for IP66 and IP67, the cradle is protected against dust and water penetration – making it a truly resilient cradle for the heavy construction industry.



Customised

With the MDS05, MDS20 and MDS30, Leica Geosystems delivers three variants of docking stations for the MCP80 3D machine control panel, facing customer needs all over the world.

leica-geosystems.com



- when it has to be **right**

Leica
Geosystems

Leica MDS05/20/30



ENVIRONMENTAL DATA

Water/Dust rating	IP66, IP67
Operation temperature	-30° - 65°C
Storage temperature	-40° - 85°C
Humidity	Damp heat (humidity condensing)* Compliance with IEC60068-2-30
Vibration	IEC 60068-2-6 5-500 Hz; 5 g; ±15 mm MIL-STD-810G.CHG-1 Fig. 514.7E-1: Category 4 Fig. 514.7E-1: Category.24
Shock	IEC 60068-2-27 60 g - 6 msec
Drops	Withstands 40 cm onto hard surfaces

MECHANICAL DATA

Dimensions (H x W x D)	156 x 192 x 64 mm
Weight	0.94 kg
Material	Cast aluminium

COMPLIANCE

CE	2014/53/EU (RED) (MDS20/30) 2014/30/EU (EMC) (MDS05)
FCC	Part 15B 22, 24, 27, 90 (MDS20/30)
RoHs	2011/65/EU & (EU) 2015/863
WEEE	2012/19/EU

STANDARDS

EMC	EN/ISO 13766-1, EN/ISO ISO13766-2, EN/ISO 14982
Machinery	EN/ISO 12100

ELECTRICAL

CPU	300 MHz TI Sitara
Internal modem	No modem in MDS05 TNC RF connector to cradle to connect to permanent roof antenna 2 x 4G LTE models of cradle available: MDS20 LTE Cat-6 4G/3G module for USA/Canada/South America/*Discontinued in EU, 4G Bands B1, 2, 3, 4, 5, 7, 12, 13, 20, 25, 26, 29, 30, 41 MDS30 LTE Cat-6 4G/3G Australia/New Zealand/Japan/Asia, 4G Bands B1, 3, 5, 7, 8, 18, 19, 21, 28, 38, 39, 40, 41
Nominal supply voltage	Min: 10+ VDC Normal operation: 10-36 VDC Max: 36 VDC
Ethernet	1 x M12
CAN	3 x M12 connectors
Serial	2 on 1 x M12 connector, 12V 1.3A output for external radio power
External GPO buttons	2 x 3 M8 connectors

*The effects of condensation are to be effectively counteracted by periodically drying out the product.

Copyright Leica Geosystems AG, 9435 Heerbrugg, Switzerland. All rights reserved. Printed in Switzerland – 2025.
Leica Geosystems AG is part of Hexagon AB. 870466en – 08.25

Leica Geosystems AG
Heinrich-Wild-Strasse
9435 Heerbrugg, Switzerland
+41 71 727 31 31

- when it has to be **right**

Leica
Geosystems